

1 OPTICAL STRUCTURES DISTRIBUTED AMONG
2 MULTIPLE OPTICAL WAVEGUIDES

3 Applicants: Christoph M. Greiner, Thomas W. Mossberg, and Dmitri lazikov

4 RELATED APPLICATIONS

5 **[0001]** This application claims benefit of prior-filed co-pending provisional App. No.
6 60/453,557 entitled "Method and apparatus for waveguide-sampling of holographic
7 spectral filters" filed 03/10/2003 in the names of Christoph M. Greiner, Thomas W.
8 Mossberg, and Dmitri lazikov, said provisional patent application being hereby
9 incorporated by reference as if fully set forth herein.

1 BACKGROUND

2 **[0002]** The field of the present invention relates to optical devices incorporating
3 distributed optical structures. In particular, distributed optical structures with diffractive
4 elements thereof distributed among multiple channel waveguides of an optical
5 apparatus are disclosed herein.

6 **[0003]** An optical apparatus comprising an optical element having one or more
7 distributed optical structures (i.e., one or more sets of diffractive elements) may be
8 configured to provide a variety of optical functionality, including spectral filtering,
9 temporal encoding, and others. Such devices, if single mode, may enable nearly
10 complete control of amplitude and phase of optical signals to achieve filtering, encoding,
11 routing, and other functions. Multimode devices may enable similar control. Examples
12 of such devices may be found in the references cited herein.

13 **[0004]** This application may be related to subject matter disclosed in: non-provisional
14 App. No. 09/811,081 entitled "Holographic spectral filter" filed 03/16/2001 in the name of
15 Thomas W. Mossberg; provisional App. No. 60/190,126 filed 03/16/2000; provisional
16 App. No. 60/199,790 filed 04/26/2000; provisional App. No. 60/235,330 filed
17 09/26/2000; provisional App. No. 60/247,231 filed 11/10/2000; non-provisional App.
18 No. 10/653,876 entitled "Amplitude and phase control in distributed optical structures"
19 filed 09/02/2003 in the names of Christoph M. Greiner, Dmitri Iazikov, and Thomas W.
20 Mossberg; non-provisional App. No. 10/229,444 entitled "Amplitude and phase control
21 in distributed optical structures" filed 08/27/2002 in the names of Thomas W. Mossberg
22 and Christoph M. Greiner, now Pat. No. 6,678,429 issued 01/13/2004; provisional App.
23 No. 60/315,302 filed 08/27/2001; provisional App. No. 60/370,182 filed 04/04/2002;
24 provisional App. No. 60/468,479 filed 05/07/2003; provisional App. No. 60/486,450 filed
25 07/10/2003; non-provisional App. No. ____/____,____ (not yet assigned; Docket No.
26 LTSM07NP) entitled "Temperature-compensated planar waveguide optical apparatus"
27 filed 03/05/2004 in the names of Dmitri Iazikov, Thomas W. Mossberg, and Christoph
28 M. Greiner; and provisional App. No. 60/452,834 filed 03/06/2003. Each of said patent
29 and said provisional and non-provisional patent applications is hereby incorporated by
30 reference as if fully set forth herein.

1 **SUMMARY**

2 **[0005]** An optical apparatus comprises an optical element having formed therein at
3 least one set of diffractive elements and at least two channel optical waveguides. Each
4 channel optical waveguide substantially confines in two transverse spatial dimensions
5 an optical signal propagating therein. Diffractive elements of each set of diffractive
6 elements are distributed among diffractive element subsets corresponding to each of
7 the multiple channel waveguides. Each diffractive element set routes, between a
8 corresponding pair of optical ports, those corresponding portions of an optical signal
9 propagating within the optical element that are received by multiple channel waveguides
10 and back-diffracted within the receiving channel waveguides by corresponding
11 diffractive element subsets. The channel optical waveguides are arranged so that an
12 optical signal entering the optical element at an input optical port first propagates
13 through a region of the optical element between the input optical port and the first ends
14 of the channel waveguides and is then incident on and received at least in part by
15 multiple channel optical waveguides. The channel optical waveguides are arranged so
16 that the corresponding routed portions of optical signal exiting the optical element at an
17 output optical port first propagate through a region of the optical element between the
18 first ends of the channel waveguides and the output optical port.

19 **[0006]** Channel waveguides may route, between a corresponding pair of optical ports,
20 portions of an optical signal transmitted by the diffractive element subsets, by
21 redirection therein or transmission therethrough. Relative spatial arrangement of the
22 ends of the channel waveguides and corresponding relative phase shifts imparted on
23 back-diffracted portions, transmitted portions, and/or redirected portions of the optical
24 signal in the channel waveguides may define at least in part a relative spatial
25 arrangement of corresponding pairs of optical ports. The ends of the channel
26 waveguides may be curved, flared, tapered, segmented, or otherwise adapted for
27 optical coupling. Relative phase shifts may be imparted by waveguide position, length,
28 modal index, longitudinal positions of diffractive element subsets, static phase shifters,
29 phase modulators, and so forth. The arrangement of the diffractive elements may
30 determine at least in part spectral and/or temporal characteristics of the optical
31 apparatus, which may be substantially independent of temperature and/or polarization,

1 or may exhibit designed dependence(s) on temperature and/or polarization. The optical
2 apparatus may include multiple sets of diffractive elements. Routing of optical signals
3 may be imaged, or non-imaged. Two or more similar optical devices may be cascaded,
4 optical output of one device serving as optical input of another.

5 **[0007]** Objects and advantages pertaining to optical structures distributed among
6 multiple optical waveguides may become apparent upon referring to the disclosed
7 embodiments as illustrated in the drawings and disclosed in the following written
8 description and/or claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Figures 1A and 1B are schematic top views of an optical device with diffractive elements and channel waveguides.

[0009] Figure 2 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0010] Figure 3 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0011] Figure 4 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0012] Figure 5 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0013] Figure 6 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0014] Figure 7 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0015] Figure 8 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0016] Figure 9 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0017] Figures 10A and 10B are schematic top views of an optical device with diffractive elements and channel waveguides.

[0018] Figure 11 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0019] Figure 12 is a schematic top view of an optical device with diffractive elements and channel waveguides.

[0020] Figure 13 is a schematic top view of an optical device with diffractive elements and channel waveguides.

1 **[0021]** Figure 14 is a schematic top view of an optical device with diffractive elements
2 and channel waveguides.

3 **[0022]** Figure 15 is a schematic top view of an optical device with diffractive elements
4 and channel waveguides.

5 **[0023]** Figure 16 is a schematic top view of an optical device with diffractive elements
6 and channel waveguides.

7 **[0024]** The embodiments shown in the Figures are exemplary, and should not be
8 construed as limiting the scope of the present disclosure and/or appended
9 claims.

1 DETAILED DESCRIPTION OF EMBODIMENTS

2 **[0025]** An optical apparatus according to the present disclosure comprises an optical
3 element having formed therein at least one set of diffractive elements and at least two
4 channel optical waveguides. Each channel optical waveguide substantially confines in
5 two transverse spatial dimensions an optical signal propagating therein. Diffractive
6 elements of each set of diffractive elements are distributed among diffractive element
7 subsets corresponding to each of at least two of the multiple channel waveguides.
8 Each diffractive element set routes, between a corresponding pair of optical ports, those
9 corresponding portions of an optical signal propagating within the optical element that
10 are received by multiple channel waveguides and back-diffracted within the receiving
11 channel waveguides by interaction between corresponding diffractive element subsets
12 and optical modes supported by the channel waveguides. The channel optical
13 waveguides are arranged so that an optical signal entering the optical element at an
14 input optical port first propagates through a region of the optical element between the
15 input optical port and the first ends of the channel waveguides and is then incident on
16 and received at least in part by multiple channel optical waveguides (into one or more
17 corresponding optical modes thereof). The channel optical waveguides are arranged so
18 that the corresponding routed portions of optical signal exiting the optical element at an
19 output optical port first propagate through a region of the optical element between the
20 first ends of the channel waveguides and the output optical port. In some instances
21 optical signals may propagate in three dimensions in these region(s); in other instances
22 these region(s) may comprise optical slab waveguide(s) (which substantially confine in
23 one transverse spatial dimension optical signals propagating in two dimensions therein).

24 **[0026]** The channel waveguides (and slab waveguide(s), if present) typically comprise
25 a core surrounded by lower-index cladding. The core is fabricated using one or more
26 dielectric materials substantially transparent over a desired operating wavelength range.
27 In some instances the cladding may include vacuum, air, or other ambient atmosphere.
28 More typically, the cladding comprises dielectric material(s). In some instances in which
29 short optical paths are employed and some degree of optical loss can be tolerated, the
30 cladding indices might be larger than the core index while still enabling the planar
31 waveguide to support guided, albeit lossy, optical modes. If slab waveguide(s) are

1 employed, the slab waveguide(s) and the channel waveguides may be formed on or
2 secured to a common substrate, for facilitating manufacture, for mechanical support,
3 and/or for other reasons.

4 **[0027]** Any of various suitable methods, including those known in the art, may be
5 employed to improve coupling of optical signals between optical modes supported by
6 the channel waveguides and optical modes propagating between optical ports and the
7 first ends of the channel waveguides (i.e. through the port-to-waveguide region). Such
8 methods may include, for example, mode-matching techniques, wherein refractive
9 indices and/or waveguide core/cladding dimensions may be suitably altered in the
10 channel waveguide(s) and/or in the port-to-waveguide region so as improve mode-
11 matching between the respective spatial modes. This may including flaring or tapering
12 of the channel waveguide cores at the first ends thereof, for example. If core and/or
13 cladding material(s) comprising the channel waveguides differ in refractive index from
14 material in the port-to-waveguide region, then curvature of the interface(s) between
15 these materials may be employed for improving mode matching. In other examples,
16 mode-matching may be improved by suitably configured segmented cores of the
17 channel waveguides (formed, for example, by removing intervening segments of the
18 core during fabrication) or by longitudinally varying core and/or cladding indices.

19 **[0028]** The set of diffractive elements of the optical apparatus may also be referred to
20 as: a distributed optical structure; a set of holographic elements; a volume hologram; a
21 distributed reflective element, distributed reflector, or distributed Bragg reflector (DBR);
22 a Bragg reflective grating (BRG); a holographic Bragg reflector (HBR); a distributed
23 Bragg structure; a mode-selective photonic bandgap crystal; a directional photonic
24 bandgap material; or other equivalent terms of art. Each diffractive element of the set
25 diffracts, reflects, scatters, or otherwise redirects a portion of an incident optical signal
26 (said process hereinafter simply referred to as diffraction). Each diffractive element of
27 the set typically comprises some suitable alteration of the planar waveguide (ridge,
28 groove, index modulation, density modulation, and so on). In the absence of the
29 multiple channel waveguides, each diffractive element may be spatially defined by a
30 virtual diffractive element contour, the shape of the contour typically being configured to
31 impart desired spatial characteristics onto the diffracted portions of the optical signal.

1 These may be 2D linear and/or curvilinear contours in a channel or slab waveguide, or
2 3D areal contours in a three dimensional optical component. In the presence of multiple
3 channel waveguides, the diffractive elements may or may not be defined by
4 corresponding virtual contours.

5 **[0029]** The diffractive elements of the set are spatially arranged with respect to one
6 another so that the corresponding portions of the optical signal diffracted by each
7 element interfere with one another, so as to impart desired spectral and/or temporal
8 characteristics onto the portion of the optical signal collectively diffracted from the set of
9 diffractive elements. The diffractive elements in the set are arranged so that an optical
10 signal, entering through an input optical port, is successively incident on diffractive
11 elements of the set, with a fraction of the incident amplitude diffracted by a diffractive
12 element while the remainder is transmitted and incident on another diffractive element,
13 and so on successively through the set of diffractive elements. The diffractive elements
14 are therefore spaced substantially longitudinally along the propagation direction of the
15 incident optical signal (in contrast to a traditional surface or thin diffraction grating, in
16 which the diffractive elements, i.e. grating lines, are spaced transversely across the
17 wavefront of the incident optical signal). If no channel waveguides are present, each
18 diffractive element is shaped to direct or route its diffracted portion of the optical signal
19 between optical ports, typically (but not necessarily) propagating back through earlier
20 diffractive elements of the set. If channel waveguides are present, the relative spatial
21 arrangement of the first ends of the channel waveguides and the spatial arrangement of
22 the diffractive elements determine the routing of diffracted portions of an optical signal
23 between optical ports. In either case (channel waveguides present or not), the relative
24 spatial arrangement (including the longitudinal spacing) of the diffractive elements of the
25 set yields desired spectral and/or temporal characteristics for the portion of an optical
26 signal routed between corresponding optical ports. For a three-dimensional optical
27 element, single-mode slab waveguide, or single-mode channel waveguide, such a set of
28 diffractive elements may be arranged to yield an arbitrary spectral transfer function (in
29 terms of amplitude and phase). In a multimode waveguide, modal dispersion and
30 mode-to-mode coupling of diffracted portions of the optical signal may limit the range of
31 spectral transfer functions that may be implemented.

1 **[0030]** It should be noted that optical ports (input and/or output) may be defined
2 structurally (for example, by an aperture, waveguide, fiber, lens, or other optical
3 component) and/or functionally (i.e., by a spatial location, convergence/divergence/
4 collimation, and/or propagation direction). While exemplary embodiments shown and/or
5 described herein maybe shown with routed optical signals imaged between
6 corresponding optical ports (i.e., focused optical beams at the ports), this need not be
7 the case. Any suitable optical port configuration, structural and/or functional, may be
8 employed in the implementation of an optical device according to the present
9 disclosure. It should also be noted that optical devices as disclosed herein may be
10 cascaded, with an output optical port of one device coupled to, or serving as, an input
11 optical port of another similar device.

12 **[0031]** An optical apparatus of the present disclosure may be conveniently described in
13 one of two ways: i) as a modification of a slab waveguide embodiment or a three
14 dimensional embodiment, wherein the 2D or 3D diffractive elements are "sampled" by
15 multiple channel waveguides formed in the optical element; or ii) as a collection of
16 multiple channel waveguide embodiments, each having diffractive elements, that
17 collectively route an optical signal. It should be noted that these differing descriptive
18 schemes, while similar, may suggest alternative schemes for fabricating optical devices
19 according to the present disclosure. However, description of devices or embodiments
20 according to one of these schemes or the other shall not be construed as limiting the
21 scope of the present disclosure or appended claims.

22 **[0032]** In an optical apparatus according to the present disclosure described according
23 to the first descriptive scheme, an optical element (a slab waveguide, for example; the
24 following discussion may be readily adapted to describe a 3D embodiment as well) has
25 a set of diffractive elements defined by corresponding 2D linear and/or curvilinear
26 contours. The elements/contours are arranged to route a diffracted portion of an optical
27 signal between corresponding optical ports of the apparatus. Multiple channel
28 waveguides are formed that each substantially span at least the region of the slab
29 waveguide where the diffractive elements are located. The channel waveguides are
30 arranged so that the incident optical signal, after entering the apparatus at an input
31 optical port and propagating through a region of the slab waveguide, is received by the

1 channel waveguides and divided among them. Each portion of the divided optical signal
2 propagates within the corresponding channel waveguide and interacts with the
3 segments of the diffractive elements that at least partly spatially overlap optical mode(s)
4 supported by the channel waveguide. Corresponding portions of the optical signal may
5 be back-diffracted within corresponding channel waveguides by the diffractive elements,
6 and the back-diffracted portions are emitted from the channel waveguides. The back-
7 diffracted and emitted portions of the optical signal propagate through a region of the
8 slab waveguide and then exit at an output optical port.

9 **[0033]** If channel waveguides are not present, the optical signal propagates freely (in
10 two unconfined dimensions in a slab waveguide; the following discussion may be readily
11 generalized to 3D optical elements with areal diffractive elements), and interacts with
12 extended portions of each diffractive element. The 2D linear and/or curvilinear shapes
13 of the diffractive elements impart spatial characteristics onto the back-diffracted portion
14 of the optical signal and determine the relative spatial arrangement of the input and
15 output optical ports. With the channel waveguides present, however, only segments of
16 the diffractive elements that at least partly spatially overlap optical mode(s) supported
17 by the channel waveguides (i.e., that are "sampled" by optical mode(s) of the channel
18 waveguides) interact with the optical signal to back-diffract a portion thereof. Spatial
19 characteristics of the back-diffracted optical signal and relative spatial arrangement of
20 the optical ports depend not only on the positions of the diffractive elements along the
21 channel waveguides, but also on the relative spatial arrangement of the first ends of the
22 channel waveguides. It should be noted that portions of the diffractive elements that are
23 not thus sampled by a channel waveguide optical mode need not be present in the
24 optical element. Diffractive elements that are sampled may be further altered, and/or
25 some of them removed altogether, so as to alter interactions with channel waveguide
26 optical modes. This is described further hereinbelow.

27 **[0034]** When forming (designing and/or fabricating) a waveguide-sampled optical
28 structure from an originally fully 2D set of diffractive elements, care should be taken to
29 accurately translate the original spectral, temporal, and/or spatial properties of the 2D
30 structure into the waveguide-sampled structure. This may include appropriately
31 adjusting the effective modal index of the channel waveguides (by means known in the

1 art) or the diffractive element spacing when sampling the 2D structure, since the indices
2 of the slab waveguide and the channel waveguides may differ. Also, any apodization
3 methods applicable to spatially extended 2D structures (and described in the cited
4 references) may not be realizable in channel waveguides, and/or may require
5 replacement by other apodization schemes more suitable for diffractive element sets in
6 channel waveguides. For example partial contour writing may be used to apodize the
7 spectral/temporal characteristics of an originally 2D diffractive structure (disclosed in
8 detail in the cited references). When a partially-written length of a diffractive element
9 contour exceeds the transverse extent of the channel waveguide optical mode, this
10 apodization approach would not be effective. Additional adaptations may be required
11 for sampling an originally 2D diffractive element set with multiple channel waveguides,
12 any suitable adaptation shall fall within the scope of the present disclosure and/or
13 appended claims.

14 **[0035]** The specific manner in which the multiple channel waveguides sample an
15 original 2D distributed optical structure may also provide a way to alter the spectral
16 and/or temporal response of the sampled structure. For example, substantially
17 uniformly spaced diffractive contours may be sampled by a curved waveguide (making
18 an angle with the diffractive elements that is sufficiently small so that functionally
19 significant fractions of light are back-diffracted into a channel waveguide optical mode),
20 thus effectively creating a chirped diffractive element set for the waveguide. This
21 approach may provide a useful pathway for achieving phase apodization when sampling
22 2D structures. This may be useful for distributed optical structures that are not formed
23 by lithography, but are instead formed using methods that do not necessarily provide
24 adequate control over individual element spacings (such as structures formed
25 interferometrically, for example). Sampling such 2D distributed optical structures at
26 appropriate angles and/or with appropriate curvatures may represent an effective way to
27 implement phase apodization.

28 **[0036]** In an optical apparatus according to the present disclosure described according
29 to the second descriptive scheme, an optical element has multiple channel waveguides
30 formed therein and a slab waveguide region. (The following discussion may be readily
31 adapted to describe a 3D embodiment as well). The channel waveguides are arranged

1 so that the incident optical signal, after entering the apparatus at an input optical port
2 and propagating through a region of the slab waveguide (propagating in two unconfined
3 spatial dimensions), is received by the channel waveguides and divided among them.
4 The optical element has a set of diffractive elements, which are distributed among
5 subsets corresponding to the channel waveguides. The diffractive elements are
6 arranged to route a diffracted portion of an optical signal between corresponding optical
7 ports of the apparatus. Each portion of the divided optical signal propagates within the
8 corresponding channel waveguide and interacts with the corresponding subset of the
9 diffractive elements. Corresponding portions of the optical signal may be back-
10 diffracted within corresponding channel waveguides by the diffractive element subsets,
11 and the back-diffracted portions are emitted from the channel waveguides. The back-
12 diffracted and emitted portions of the optical signal propagate through a region of the
13 slab waveguide and then exit at an output optical port. Diffractive elements belonging to
14 distinct diffractive element subsets may comprise distinct elements, or may comprise
15 distinct portions of a diffractive element that intersects multiple channel waveguides.

16 **[0037]** The set of diffractive elements of the optical apparatus imparts designed
17 spectral and/or temporal characteristics onto the diffracted portion of the optical signal.
18 Spatial routing of the diffracted portion of the optical signal between optical ports is
19 determined by the relative spatial arrangement of the first ends of the multiple channel
20 optical waveguides, as well as the arrangement of the diffractive element subsets
21 thereof. The arrangement of channel waveguides and diffractive elements may be
22 designed (by computer generation, for example) so as to provide optimal routing,
23 imaging, or focusing of the optical signal between an input optical port and a desired
24 output optical port, thus reducing or minimizing insertion loss of the apparatus. A wide
25 range of fabrication techniques may be employed for forming sets of diffractive
26 elements and channel waveguides of various sorts, and any suitable technique(s) may
27 be employed while remaining within the scope of the present disclosure and/or
28 appended claims. The following are exemplary only, and are not intended to be
29 exhaustive.

30 **[0038]** Diffractive elements may be formed lithographically on the surface of a slab or
31 channel optical waveguide, or at one or both interfaces between core and cladding of

1 such waveguides. Diffractive elements may take the form of trenches or ribs at the
2 surface of the core, with material of differing index filling the trenches or the spaces
3 between the ribs (the filling material may be cladding material, or some other optical
4 material). Diffractive elements may be formed lithographically in the interior of the core
5 layer of the waveguide using one or more spatial lithography steps performed after an
6 initial partial deposition of the core layer material. Diffractive elements may be formed
7 by projecting ultraviolet light or other suitable radiation through an amplitude and/or
8 phase mask so as to create an interference pattern within the waveguide (fabricated at
9 least in part with suitably sensitive material) whose fringe contours match the desired
10 diffractive element contours. Alteration of the refractive index by exposure to ultraviolet
11 or other radiation results in index-modulated diffractive elements. The mask may be
12 zeroth-order-suppressed according to methods known in the art, including the arts
13 associated with fabrication of fiber Bragg gratings. The amplitude and/or phase mask
14 may be produced lithographically via laser writer or e-beam, it may be interferometrically
15 formed, or it may be formed by any other suitable technique. In instances where
16 resolution is insufficient to produce a mask having required feature sizes, a larger scale
17 mask may be produced and reduced to needed dimensions via photoreduction
18 lithography, as in a stepper, to produce a mask at the needed scale. Diffractive
19 elements may be formed by molding, stamping, impressing, embossing, or other
20 mechanical processes. Many approaches to the creation of refractive index
21 modulations or gratings are known in the art and may be employed in the fabrication of
22 diffractive element sets.

23 **[0039]** Irradiation-produced refractive index modulations or variations for forming
24 diffractive elements will optimally fall in a range between about 10^{-4} and about 10^{-1} ;
25 however, refractive index modulations or variations outside this range may be employed
26 as well. Refractive index modulations or variations may be introduced by light of any
27 wavelength (including ultraviolet light) that produces the desired refractive index
28 changes, provided only that the photosensitive material employed is suitably stable in
29 the presence of light in the desired operating wavelength range of the spectral filter.
30 Exposure of a complete set of diffractive elements to substantially spatially uniform,
31 refractive-index-changing light may be employed to tune the operative wavelength

1 range of the diffractive element set. Exposure of the diffractive element set to spatially
2 non-uniform refractive-index changing light may be employed to chirp or otherwise
3 wavelength-modulate the spectral filter.

4 **[0040]** The two descriptive schemes may suggest distinct approaches for fabricating
5 an optical apparatus according to the present disclosure. It may be advantageous in
6 some circumstances to first form the set of channel waveguides and then form the
7 diffractive elements, while in other circumstances it may be advantageous to first form
8 the diffractive elements, and then form the channel waveguides. In some
9 circumstances, it may be advantageous to form the diffractive elements as full 2D or 3D
10 contours that are "sampled" by the channel waveguides, while in other instances it may
11 be advantageous to only form diffractive elements at locations where they would
12 interact with optical modes supported by the channel waveguides. Any of these
13 fabrication schemes, as well as other suitable fabrication schemes, shall fall within the
14 scope of the present disclosure and/or appended claims.

15 **[0041]** Figure 1A is a schematic top view of an exemplary two-dimensional slab
16 waveguide structure. The waveguide lies in the plane defined by the x-axis and y-axis
17 shown in Figure 1A. The waveguide structure, specifically its core, occupies a certain
18 region of the xy-plane and has a thickness Δz . The diffractive elements contours 106
19 (substantially concentric arcs in this example centered at 107), that constitute a
20 distributed optical structure 105, may comprise trenches or ribs in the core layer or may
21 comprise bulk refractive index changes in the core material induced by optical exposure
22 or other means. For a single-mode slab waveguide, the thickness Δz is typically 1 to 8
23 times the in-medium design wavelength of the device. For a multimode slab
24 waveguide, Δz may be on the order of 30 to 60 times the in-medium design wavelength
25 of the device. At a typical telecommunications wavelengths ($\lambda_{\text{air}} \sim 1.5 \mu\text{m}$), the
26 thickness of the planar waveguide may be about $4 \mu\text{m}$ if the waveguide medium is silica
27 and single-mode operation is desired, for example.

28 **[0042]** In Figure 1A, light enters the planar waveguide from an optical port 101.
29 Optical port 101 may comprise a channel waveguide, an edge mounted optical fiber, the
30 focal spot of a free-space light source, or other suitable component and/or arrangement.

1 The entering optical signal (diverging input beam 111) propagates and expands (in the
2 xy-plane) in slab waveguide region 103. At the end of region 103, the input beam 111
3 is incident on and received by a manifold of channel waveguides 104, which in this
4 example form a dense waveguide array that samples the distributed optical structure
5 105. Portions of the optical signal propagating in the channel waveguides interact with
6 and are back-diffracted from the distributed optical structure 105 where the elements
7 thereof at least partly overlap optical modes supported by the channel waveguides. The
8 first ends of channel waveguides 104 are arranged on a virtual contour 108, which is
9 defined so that light emitted from the channel waveguides (having been back-diffracted
10 within the channel waveguides by the distributed optical structure) forms an output
11 beam 112 that exits the device via output port 102. At output port 102 the portion of the
12 optical signal thus routed by the diffractive element set may enter a channel waveguide,
13 an optical fiber, a free space optical assembly, or other output apparatus. In forming
14 channel waveguides 104, lateral optical confinement may be achieved by removal of
15 core material from regions between the channel waveguides (by etching or other
16 suitable processes), or lateral optical confinement may be provided using any other
17 suitable fabrication scheme. Portions of distributed optical structure 105 that lie
18 between channel waveguides 104 may be removed or left in place, as needed or
19 desired (left in place in the exemplary embodiment of Figure 1). Core and/or cladding
20 materials forming slab waveguide region 103 may be the same as those forming
21 channel waveguides 104, or they may differ.

22 **[0043]** The virtual contour 108 for locating the ends of the channel waveguides 104
23 may be chosen so as to spatially redirect the wave front of the input signal to the output
24 port 102. In this example, the contour 108 is a circular arc substantially concentric with
25 the contours of distributed optical structure 105 (centered at 107, approximately midway
26 between the ports 101 and 102). Such a contour may provide (approximately) unit-
27 conjugate-ratio imaging between the optical ports. A circular contour does not provide
28 optimal mapping of the input wavefront to the output port, and better optimized contours
29 may be designed, for example in a manner similar to the design of aspheric reflective
30 optics. For example, segments of an ellipse may serve as contour 108, with optical
31 ports 101 and 102 located at the ellipse foci. An imaging contour (with focused optical

1 beams at the optical ports) is not necessarily required. Any suitable beam size, shape,
2 divergence, convergence, collimation, and/or propagation direction may be
3 implemented by suitably configuring virtual contour 108 and the ends of channel
4 waveguides 104, and such implementations shall fall within the scope of the present
5 disclosure and/or appended claims. In this exemplary embodiment, the channel
6 waveguides are spaced with equal angular displacement about a common intersection
7 point coincident with the center of curvature 107, so that if extended from contour 108
8 they would contain point 107. Other suitable angular spacings, including irregular
9 angular spacings, shall fall within the scope of the present disclosure and/or appended
10 claims.

11 **[0044]** As further described hereinbelow, it is the port-to-port relative phases of the
12 portions of the optical signal back-diffracted from the diffractive element subsets that
13 determine (along with the spatial characteristics of the input optical signal and the
14 channel waveguide optical modes) the spatial properties of the optical output of the
15 device. A virtual contour (such as contour 108) is merely a convenient reference from
16 which to measure such relative phase shifts. Port-to-port relative phase shifts include
17 port-to-waveguide phase shifts, phase shifts imparted by the waveguides, and
18 waveguide-to-port phase shifts. A virtual contour, if applicable to a particular
19 embodiment, may characterize the port-to-waveguide and waveguide-to-port phase
20 shifts for the back-diffracted portion of the optical signal. The exemplary embodiments
21 disclosed herein are shown with virtual contours defined by the ends of the channel
22 waveguides. However, embodiments for which such a contour has not been defined, or
23 for which such a contour may not be appropriate, shall fall within the scope of the
24 present disclosure and/or appended claims.

25 **[0045]** A distributed optical structure implemented in multiple channel optical
26 waveguides may exhibit polarization-dependent spectral, temporal, or other optical
27 properties (or lack thereof) that differ in polarization dependence from properties of such
28 structures implemented in a slab waveguide. These differences may be exploited for
29 imparting a design polarization dependence into an optical device, or for reducing or
30 substantially eliminating polarization dependent optical device properties. Use of

1 channel waveguides may facilitate reduction or substantial elimination of such
2 polarization dependences, if needed or desired.

3 **[0046]** In another exemplary embodiment, illustrated schematically in Figure 1B, the
4 virtual contour 108 along which the first ends of the channel waveguides 104 are
5 arranged is derived by interfering input and output optical beams in the optical element.
6 At operating wavelength of interest, a first numerically-simulated optical field having
7 spatial and spectral properties of the desired input optical beam is interfered
8 (computationally) with a second numerically-simulated field that exhibits the spatial and
9 spectral properties of the desired output optical beam. Optical fields from actual light
10 sources may also be used for generating an interferogram. Numerically simulated
11 generating fields may be employed that may not be readily obtainable from an actual
12 light sources or in waveguide geometries of interest. First, the interference pattern
13 between the two optical fields is calculated. For the specific case of two interfering
14 fields the interference pattern consists of three contributions: i) a portion varying
15 spatially in proportion to the intensity of the first field; ii) a portion varying spatially in
16 proportion to the intensity of the second field; and iii) a portion that depends on the
17 phase difference between the two fields, and which typically varies spatially on a
18 relatively rapid scale (wavelength-scale). This third portion is referred to as an
19 interferogram. Only the interferogram is employed for determining the shape of virtual
20 contour 108. The amplitude of the interferogram itself, at any given spatial position, is
21 proportional to a product of the optical field amplitudes of the interfering beams at that
22 position and a trigonometric function (such as a cosine) of the phase difference between
23 the interfering fields at that position. The latter phase-difference-dependent factor shall
24 be referred to as the interferogram phase function, while the product of the optical field
25 amplitudes shall be referred to as the interferogram amplitude function. The amplitude
26 function of the interferogram is set to a constant. The calculated interferogram phase
27 function may be digitized using points corresponding to maxima or minima (or other
28 level contour if period doubling is avoided). If maxima are used, the resulting computed
29 structure comprises a set of lines or curves on which the phase difference between the
30 two interfering beams is an integer multiple of 2π . At some desired distance away from
31 the input port one of the aforementioned lines or curves is chosen as contour 108, along

1 which the first ends of channel waveguides 104 are arranged. Figure 1B shows a
2 specific embodiment in which virtual contour 108 was derived by interfering input and
3 output beams crossing at about a 90° angle. As noted above, virtual contour 108 is
4 merely a convenient reference from which to measure relative phase shifts, and may be
5 regarded as somewhat arbitrary.

6 **[0047]** Channel waveguides 104 are aligned so that each waveguide axis at its first
7 end is substantially parallel to the bisector of the local wavevectors of the input and
8 output optical fields at the center of the first end of the channel waveguide. The mode
9 width of the channel waveguides at their first ends determines the divergence of an
10 optical beam emerging from it. The mode widths may be chosen such that the desired
11 locations of the input and output optical ports are substantially within this divergence
12 angle, and the channel waveguide axial alignments deviate from the bisector provided
13 this condition is substantially satisfied. The channel waveguide cores may be flared or
14 tapered at the first ends thereof to achieve the desired beam divergence. It should be
15 noted that an interferometrically derived virtual contour 108 may enable efficient optical
16 coupling between pairs of corresponding input and output ports even at relatively large
17 angles (outside the paraxial approximation), for spatially extended input and output
18 ports (not point sources), as well as imaging of input-output port pairs having different
19 beam waists and/or wavefronts. Note further, that, while most embodiments in the
20 present disclosure depict devices wherein a focused input beam is routed to a focused
21 output beam, it is also possible, using the present invention, to design devices with input
22 and output beams of differing wavefront properties, e.g., converging, collimated, or
23 diverging output beams routed from converging, collimated, or diverging input beams.
24 All such combinations may be implemented in any of the exemplary embodiments
25 disclosed herein, and shall within the present disclosure and/or appended claims.

26 **[0048]** Another exemplary embodiment according to the present disclosure is shown
27 schematically in Figure 2. An optical signal enters at optical port 201, from which
28 diverging optical beam 211 propagates through slab waveguide region 203. In this
29 exemplary embodiment channel waveguides 204, have flared (equivalently, tapered)
30 ends to facilitate improved input beam coupling efficiency and emitted optical signal
31 divergence angle, and are spatially offset from each other so as to be consistent with

1 the resolution of the lithographic, stamping/embossing, or other process employed for
2 fabrication. The end faces of the channel waveguides may be curved for improved
3 input beam coupling efficiency, if appropriate. The distributed optical structure is
4 divided into diffractive element subsets 205 corresponding to channel waveguides 204.
5 The diffractive elements may substantially span the lateral extent of the propagating
6 modes supported by the channel waveguides in this example. The diffractive elements
7 206 in this example are linear segments substantially perpendicular to the
8 corresponding waveguide axis (other suitable arrangements, shapes, and/or
9 orientations of the diffractive elements may be employed). In addition, geometries
10 where diffractive elements are of smaller lateral extent than the mode field, including
11 situations where the diffractive elements extend only over the channel waveguide core
12 or a portion thereof, or over any sub-portion of the channel waveguide transverse modal
13 profile, shall fall within the scope of the present disclosure and/or appended claims.
14 The ends of the waveguides 204 are arranged on virtual contour 208, a circular arc
15 centered at 207 in this example. Other shapes, positions, and/or arrangements of
16 virtual contour 208 may provide improved input/output optical coupling and shall fall
17 within the scope of the present disclosure and/or appended claims.

18 **[0049]** At any given position in a device output plane 209, the total output field
19 comprises a coherent sum of all the optical fields back-diffracted from diffractive
20 element subsets 205 and emerging from channel waveguides 204. Stated otherwise,
21 the arrangement of channel waveguide ends on contour 208 may be regarded as
22 forming a generalized optical structure wherein an input optical signal is divided among
23 multiple device apertures (i.e., channel waveguide ends), and the amplitude, phase, and
24 spectral bandpass of each device aperture (i.e., each channel waveguide output) is
25 determined by the channel waveguides 204 and the corresponding diffractive element
26 subsets 205 thereof. Since the diffractive element subsets 205 may be completely
27 independent of one another, powerful phase and amplitude manipulation of the back-
28 diffracted field at the device output port may be achieved (for example, by employing
29 methods to control the amplitude and phase of the diffractive elements, as disclosed in
30 the references cited hereinabove, for tailoring of the back-diffracted portions of the
31 optical signal). Manipulating the phase, amplitude, and spectral bandpass of the

1 channel waveguide output fields also enables general control of shape, position, and
2 temporal/spectral characteristics of the device output at port 202 in the device output
3 plane 209. General control over the relative phases of the back-diffracted portion of the
4 optical signal provided general control over the wavefront and propagation direction of
5 the total back-diffracted optical field emerging from the channel waveguides. Methods
6 of varying complexity for accomplishing control of the phase, amplitude, and/or spectral
7 bandpass of the channel waveguide output signals are described further hereinbelow.

8 **[0050]** In a first example, shown in Figure 2, it may be assumed that all diffractive
9 elements subsets 205 are located equal distances from the ends of the corresponding
10 channel waveguides, i.e., from virtual contour 208. Consequently, relative phase shifts
11 imparted by the channel waveguides 204 on the back-diffracted portions of the optical
12 signal arise only from differences in optical path length between optical port 201 and the
13 ends of the channel waveguides. In this case, the location of device output port 202
14 corresponds to a zeroth order of the set of device apertures defined by the ends of the
15 channel waveguides. The relative spatial arrangement of optical ports 201 and 202 is
16 determined by the imaging properties of virtual contour 208. In the illustrated example,
17 where contour 208 is a circular arc centered at 207, ports 201 and 202 are located at
18 output plane 209 substantially symmetrically positioned about center-of-curvature 207.
19 Note that, when the angular spacing of the ends of channel waveguide 204 (as
20 measured from center of curvature 207) is substantially uniform, higher-order outputs
21 may appear at output plane 209. These may be used conveniently as additional device
22 optical ports, or, if deemed undesirable, higher-order outputs may be suppressed, by
23 non-uniform angular spacing of the ends of channel waveguides 204, by increasing the
24 width of the ends of the channel waveguides by flaring or tapering, for example) so that
25 higher-order outputs lie outside the divergence angles of the channel waveguides, or by
26 other suitable means.

27 **[0051]** Figure 3 schematically illustrates another exemplary embodiment. Unless
28 otherwise stated, the device of Figure 3 resembles the device of Figure 2 (with
29 analogous numbering of elements). The substantive difference between the devices of
30 Figures 2 and 3 is that the corresponding diffractive element subsets 205 of channel
31 waveguides 204 are not located at equal distances from the ends of the channel

1 waveguides (i.e., from virtual contour 208). As in the embodiment of Figure 2, an
2 entering optical signal propagates through slab waveguide region 203 and is divided
3 among channel waveguides 204. Portions of the optical signal are back-diffracted from
4 corresponding diffractive element subsets 205 if resonant therewith. The net optical
5 path length traveled by back-diffracted light within the channel waveguides is twice the
6 separation between waveguide end and an effective point of reference of the diffractive
7 element subset (multiplied by the appropriate modal index). The differing optical paths
8 among the diffractive element subsets 205 impart additional relative phase shifts among
9 the back-diffracted portions of the optical signal, in addition to that due to differing
10 propagation lengths in the slab waveguide region. Such phase differences result in
11 shifting of the relative spatial arrangement of the optical ports, e.g., spatially altered
12 and/or shifted output beam 312 (altered and/or shifted relative to the original output
13 beam 212), and/or a spatially altered and/or shifted device output port 302 (from the
14 original output port 202 with no phase differences imparted by the channel waveguides
15 or diffractive element subsets).

16 **[0052]** The particular set of phase shifts imparted into the back-diffracted portions of
17 the optical signal determine (at least in part) the spatial alteration and/or shift (i.e., the
18 relative spatial arrangement) of the optical ports. For example, if the imparted phase
19 shifts vary linearly across the set of channel waveguides, then the shifted optical beam
20 and corresponding optical port will substantially retain its shape and be shifted to a
21 different location. A set of phase shifts may be imparted that leave the optical port in its
22 original location but alter its shape (i.e., alter the transverse spatial profile of the back-
23 diffracted optical signal). Any set of relative phase shifts may be employed to yield a
24 desired spatial alteration and/or shift of an optical port, and shall fall within the scope of
25 the present disclosure and/or appended claims. If the diffractive element subsets are
26 positioned along the channel waveguides so that the net (i.e., round trip or double pass
27 for back-diffracted optical signals) relative phase shifts differ by less than 2π , then the
28 optical output may be referred to as zeroth-order. Optical output resulting from relative
29 phase shifts differing by more than 2π may be referred to as higher-order (1st, 2nd, ...)
30 as appropriate. Higher-order optical output may typically exhibit a greater degree of

1 chromaticism than zeroth-order optical output, which may be desirable or undesirable
2 depending on the particular use of the optical device.

3 **[0053]** It should be noted that while these descriptions refer to fixed input port and a
4 spatially altered and/or shifted output port, they may equally well describe a fixed output
5 port and a spatially altered and/or shifted input port, or spatially altered and/or shifted
6 input and output ports. In general, the relative spatial arrangement of the ends of the
7 channel waveguides and any relative phase shifts imparted in the channel waveguides
8 define a relative spatial arrangement of pairs of optical ports.

9 **[0054]** Rather than physically shifting the positions of the diffractive element subsets
10 205 at different locations with respect to virtual contour 208, relative phase shifts among
11 the back-diffracted portions of the optical signal may also be introduced by other means,
12 and may be employed for yielding permanent or temporary relative phase shifts among
13 the back-diffracted portions of the optical signal. The ends of channel waveguide 204
14 may be spatially shifted relative to one another, for example, and may not necessarily
15 correspond to contour 208 (or any other readily-defined contour). Static phase shifters
16 may be incorporated into the channel waveguides in various ways, for example taking
17 the form of waveguide segments having a differing modal index and various lengths.
18 Such waveguide segments may be formed in any suitable way, including but not limited
19 to variations in channel waveguide structure (core and/or cladding), use of varying
20 waveguide materials (core and/or cladding), modification of waveguide materials (core
21 and/or cladding, by densification, irradiation, etc), and so forth. Temporary phase shifts
22 may be imparted using phase modulators of any suitable type, including but not limited
23 to electro-optic modulators, photoelastic modulators, non-linear optical modulators, and
24 so on, and impart relative phase shifts in response to applied control signals. Such
25 phase shifters or modulators may be positioned so as to interact with optical signals
26 propagating in the corresponding channel waveguides at contour 208 or between
27 contour 208 and corresponding diffractive element subsets 205. Imparting reversible
28 relative phase shifts enables switching of device output port 302 among differing
29 locations (or equivalently, switching a device input port among differing locations). This
30 may be useful, for example, for switching between different input and/or output optical
31 waveguides.

1 **[0055]** Figure 4 illustrates schematically an exemplary embodiment in which individual
2 phase shifters or modulators 413 are positioned at each channel waveguide 204. All
3 phase shifters/modulators 413 are shown as having the same physical length
4 therethrough. To impart the desired relative phase shifts and spatially shift the output
5 beam 412 and output optical port 402, static phase shifters would exhibit differing modal
6 indices, while phase modulators would require differing control signal levels applied to
7 each modulator. In the exemplary embodiment illustrated schematically in Figure 5,
8 phase shifters/modulators 513 are shown as having differing physical lengths
9 therethrough. Imparted relative phase shifts may arise from the differing path lengths,
10 so that a single modal index may be employed in static phase shifters, or a single
11 control signal level may be applied to phase modulators. While
12 phase shifters/modulators 513 are shown in Figure 5 as a single contiguous element
13 spanning the channel waveguides, they could equivalently comprise corresponding
14 distinct elements for the channel waveguides. It should be noted that numerous
15 variations and/or combinations of the methods illustrated in Figures 4 and 5, including
16 schemes wherein the phase shifters/modulators are placed in the slab waveguide
17 region, shall fall within the scope of the present disclosure and/or appended claims.

18 **[0056]** In the exemplary embodiment schematically illustrated in Figure 6, diffractive
19 element subsets 205 are positioned along the corresponding channel waveguides 204
20 so that the relative phase shifts (round trip, or double pass phase shifts for back-
21 diffracted optical signals) for adjacent channel waveguides increases by $2\pi m$, where m
22 is an integer (not zero). In this case, the device input and output ports 601 and 602,
23 respectively, are located substantially symmetrically about center-of-curvature 207 of
24 virtual contour 208. This relative positioning of input and output ports corresponds to
25 the m^{th} order output of the set of device apertures defined by the ends of the channel
26 waveguides. The spectral bandpass of the portion of the optical signal routed to this
27 point is given by the smaller of the spectral bandpass of the corresponding diffractive
28 element subsets 205 and $\Delta\lambda = \lambda/Nm$, where λ is a resonant wavelength of the diffractive
29 element set and N is the total number of channel waveguides. By altering the relative
30 phase shifts among the back-diffracted portions of the optical signal, as described for

1 Figures 3 through 5, the relative spatial arrangement of optical ports 601 and 602 may
2 be modified.

3 **[0057]** Once the optical signal has been divided among the channel waveguides 204,
4 only the relative optical paths traversed by the optical signal are relevant to the function
5 of the optical device. In the exemplary embodiment schematically illustrated in Figure 7,
6 the channel waveguides 204 are oriented radially at virtual contour 208 (as in the
7 previous Figures), but then curve so as to become substantially parallel to one another
8 (in this example). This arrangement may enable reduction of overall device size, while
9 functioning in a manner analogous to any of the previous exemplary embodiments.

10 **[0058]** In the exemplary embodiment schematically illustrated in Figure 8, diffractive
11 element subsets 205 are modified according to the teachings of various of the
12 references cited hereinabove for controlling the amplitude and phase of portions of the
13 optical signal back-diffracted by diffractive element subsets (i.e., for apodization). In this
14 particular example the transverse extent of individual diffractive elements 206 are
15 modulated as a function of position along the corresponding channel waveguide 204,
16 and may also exhibit position-dependent longitudinal offsets (relative to nominally
17 uniform element spacing) to yield desired back-diffracted optical field phase shifts for
18 overall customization of a spectral transfer function of the diffractive element subset.
19 Many other types of modifications and/or adaptations may be employed for amplitude
20 and/or phase manipulation of the back-diffracted optical signal are disclosed in the cited
21 references, and shall fall within the scope of the present disclosure and/or appended
22 claims. Such customization (i.e., apodization) may be common to all channel
23 waveguides or may differ among the channel waveguides to achieve a desired overall
24 spectral-spatial transfer function for the device. Various modifications disclosed for
25 other exemplary embodiments may be combined with those illustrated in Figure 8 in any
26 suitable way.

27 **[0059]** In the exemplary embodiment schematically illustrated in Figure 9, the channel
28 waveguides 204 include corresponding broadband reflectors 907. As in previous
29 exemplary embodiments, an entering optical signal is divided among the channel
30 waveguides 204, and portions are back-diffracted by diffractive element subsets 205

1 and routed to an output port (906 in this example, the location of which may be
2 determined in any manner disclosed herein). Portions of the optical signal transmitted
3 by the diffractive element subsets 205 are redirected by broadband reflectors 907,
4 emitted from the ends of channel waveguides 204, and exit the planar waveguide at
5 optical port 902. The broad band reflectors 907 may be formed in any suitable manner,
6 including but not limited to thin-film dielectric mirrors (butted against a second end of the
7 channel waveguides or directly coated onto them), metal mirrors or coatings (such as
8 gold), a diffraction grating in Littrow arrangement, a broadband distributed reflector, and
9 so forth. These and other suitable broadband reflectors shall fall within the scope of the
10 present disclosure and/or appended claims. In this example, the channel waveguides
11 have the same optical path between virtual contour 208 and the broadband reflectors
12 907, so that optical port 902 receives zeroth order output of the broadband redirected
13 portions of the optical signal from the channel waveguides. Many other arrangements
14 may be implemented for determining the relative spatial arrangement of ports 901 and
15 902, including any of the schemes described above for the back-diffracted portions of
16 the optical signal. Relative phase shifts may be imparted on the redirected portions of
17 the optical signal by differing positions of the broadband reflectors along the
18 corresponding channel waveguides, phase shifters, and/or phase modulators. Phase
19 modulators may be employed for shifting the relative spatial arrangement of
20 corresponding pairs of optical ports in response to applied control signal(s).

21 **[0060]** The exemplary embodiment of Figure 9 may function as an optical multiplexer
22 or demultiplexer. To function as a channel-dropping demultiplexer, optical port 901
23 comprises an input port, optical port 902 comprises an output port, and optical port 906
24 comprises a dropped-channel port. To function as a channel-adding multiplexer, optical
25 port 902 comprises an input port, optical port 901 comprises an output port, and optical
26 port 906 comprises an added-channel port. It should be noted that for any of the
27 exemplary embodiments disclosed herein, input ports and output ports may generally
28 be interchanged. A diffractive element set, set of reflectors, or other optical structure
29 that routes an optical signal or portion thereof between a pair of optical ports can
30 generally do so in either direction. Therefore, labeling of ports as input or output may
31 be somewhat arbitrary, or may depend on the manner of use of the optical apparatus.

1 **[0061]** In the exemplary embodiment schematically illustrated in Figures 10A and 10B,
2 back-diffracted portions of the optical signal are routed between optical ports 1001 and
3 1002, while portions of the optical signal that are transmitted by the diffractive element
4 subsets 205 propagate along channel waveguides 204 to their second ends. Upon
5 being emitted from the second ends of the channel waveguides, the transmitted
6 portions of the optical signal propagate through a second slab waveguide region 1006.
7 The relative spatial arrangement of the first ends of the channel waveguides, the
8 relative spatial arrangement of the second ends of the channel waveguides, and phase
9 shifts imparted on the transmitted portions of the optical signal by the channel
10 waveguides define the relative spatial arrangement of optical ports 1001 and 1007.
11 Optical port 1007 may receive zeroth order transmitted optical signal or higher-order
12 transmitted optical signal, depending on the relative imparted relative phase shifts.
13 Relative phase shifts may be imparted on the transmitted portions of the optical signal
14 by static phase shifters 1008, shown with differing lengths in Figures 10A and 10B (to
15 compensate for the differing lengths of waveguides 204). In Figure 10A, phase shifters
16 1008 comprise channel waveguide core segments having an increased refractive index,
17 yielding a larger modal index. In Figure 10B, phase shifters 1008 comprise channel
18 waveguide core segments having an increased width, yielding a larger modal index.
19 However, other various means may be employed for imparting desired relative phase
20 shifts onto transmitted portions of the optical signal, analogous to those disclosed
21 hereinabove for back-diffracted and/or redirected optical signals and employing differing
22 path lengths, phase shifters, and/or phase modulators. For example, relative phase
23 shifts may be imparted by the lengths of the channel optical waveguides. In the
24 example of Figure 11, the lengths of the channel waveguides are made substantially
25 equal (i.e., zero relative phase shifts). In the example of Figure 12, the relative spatial
26 arrangement of the second ends of the channel optical waveguides about slab
27 waveguide region 1206 compensates for non-zero relative phase shifts imparted by
28 differing channel waveguide lengths, yielding zeroth order optical output at optical port
29 1007. This latter scheme relies on a modal index within the slab waveguide region that
30 differs from the modal index of the channel waveguides to enable phase compensation.
31 Various combinations of higher- or lower-index slab waveguide region (relative to the

1 channel waveguide modal index) and corresponding relative spatial arrangement of the
2 second ends of the channel waveguides shall fall within the scope of the present
3 disclosure and/or appended claims.

4 **[0062]** In the exemplary embodiment schematically illustrated in Figure 13, phase
5 shifters/modulators 1306 are employed for defining the relative spatial arrangement of
6 optical ports 1301 and 1302 (for the back-diffracted portions of the optical signal).
7 Phase shifters/modulators 1307 are employed for defining the relative spatial
8 arrangement of optical ports 1301 and 1303 (for the transmitted portions of the optical
9 signal). Phase shifters/modulators 1307 may partly compensate for phase shifts
10 imparted on transmitted portions of the optical signal by phase shifters/modulators
11 1306. Use of phase modulators enables controlled shifting of the relative spatial
12 arrangements of optical ports 1301, 1302, and 1303.

13 **[0063]** Any of the exemplary embodiments of Figures 10, 11, 12, and 13 may function
14 as an optical multiplexer or demultiplexer. To function as a channel-dropping
15 demultiplexer, optical port 1001 or 1301 comprises an input port, optical port 1002 or
16 1302 comprises a dropped-channel port, and optical port 1007 or 1303 comprises an
17 output port. To function as a channel-adding multiplexer, optical port 1002 or 1302
18 comprises an added-channel port, optical port 1001 or 1301 comprises an output port,
19 and optical port 1007 or 1303 comprises an input port. As stated hereinabove,
20 designation of an optical port as an input or output may vary with the particular use of a
21 particular device. In any of the embodiments of Figures 10, 11, 12, or 13, the second
22 ends of the channel waveguides may be structurally adapted for optical coupling with
23 the corresponding optical port. Such adaptations may include flaring or tapering of the
24 end of the waveguide, and/or curved waveguide end faces. Any of the exemplary
25 embodiments of Figures 10, 11, 12, and 13 may be further modified to include additional
26 diffractive element sets and one or more additional optical port(s) near optical port 1007
27 (or 1303 in Figure 13). Such additional diffractive element sets may route back-
28 diffracted portions of optical signals between optical port 1007 (or 1303 in Figure 1303)
29 and one of the additional ports. Additional optical functionality may be implemented by
30 back-diffraction of optical signals entering the channel waveguides at either of the ends
31 thereof.

1 **[0064]** In the exemplary embodiment illustrated schematically in Figure 14, the optical
2 element has two sets of diffractive elements. A first set of diffractive elements
3 comprises diffractive element subsets 1405, while a second set of diffractive elements
4 comprises diffractive element subsets 1406. The entering optical signal is divided
5 among the waveguides 204, and first portions are back-diffracted from diffractive
6 element subsets 1405 and thereby routed between optical ports 1401 and 1402.
7 Second portions of the optical signal are back-diffracted from diffractive element
8 subsets 1406 and thereby routed between optical ports 1401 and 1403. The distinct
9 diffractive element sets typically impart differing spectral and/or temporal characteristics
10 onto the corresponding back-diffracted portions of the optical signal. For each of the
11 back-diffracted portions of the optical signal, all of the modifications, adaptations, and/or
12 arrangements disclosed hereinabove may be employed. One or more additional
13 diffractive element sets (comprising corresponding diffractive element subsets) may be
14 present, and may back-diffract additional corresponding portions of the optical signal
15 and thereby route them between corresponding pairs of optical ports. The channel
16 waveguides may include broadband reflectors for redirecting the transmitted portions of
17 the optical signal, or may emit the transmitted portions from their second ends. Such
18 embodiments (including that of Figure 14) may be function as optical multiplexers
19 and/or demultiplexers. To function as a demultiplexer, optical port 1401 comprises an
20 input port, optical port 1402 comprises a first channel output port, and optical port 1403
21 comprises a second channel output port. To function as a multiplexer, optical port 1402
22 comprises a first channel input port, optical port 1403 comprises a second channel input
23 port, and optical port 1401 comprises an output port. Additional diffractive element sets
24 (as described above) enable multiplexing/demultiplexing of additional channels. The
25 embodiment of Figure 14 employs diffractive elements subsets occupying distinct
26 segments along the length of the channel waveguides (i.e., stacked diffractive element
27 subsets). Analogous embodiments may be constructed in which the multiple diffractive
28 element subsets are overlaid or interleaved on each channel waveguide. Alternatively,
29 multiple distinct diffractive element sets may be interleaved among different channel
30 optical waveguides. For example, each channel waveguide may include a diffractive
31 element subset from only one of the diffractive element sets present in the optical

1 element. In a further variation of the exemplary embodiment of Figure 14, the diffractive
2 element subsets 205 may be chirped or otherwise vary in their longitudinal spacings
3 along channel waveguides 204, to achieve desired temporal and/or spectral
4 characteristics. For example, if diffractive element subsets 205 are chirped at differing
5 rates along the lengths of the corresponding channel waveguides 204, differing spectral
6 portions of the back-diffracted optical signal will be directed to differing output port
7 locations. These and other such modifications to the diffractive element subsets 205
8 shall fall within the scope of the present disclosure and/or appended claims.

9 **[0065]** The exemplary embodiment schematically illustrated in Figure 15 may function
10 as an add/drop multiplexer. An optical signal entering optical port 1501 and transmitted
11 by diffractive element subsets 205 is routed to optical port 1502 by broadband reflectors
12 1509. An optical signal entering optical port 1501 and back-diffracted by diffractive
13 element subsets 205 is routed to optical port 1506. An optical signal entering optical
14 port 1508 and back-diffracted by diffractive element subsets 205 is routed to optical port
15 1502. In this way, so-called express optical channels may be routed between optical
16 ports 1501 and 1502, an added optical channel may be routed between optical ports
17 1508 and 1502, while a dropped optical channel may be routed between optical ports
18 1501 and 1506. For each of the back-diffracted and transmitted portions of the optical
19 signal, all of the modifications, adaptations, and/or arrangements disclosed hereinabove
20 may be employed.

21 **[0066]** Optical apparatus as disclosed herein may typically exhibit temperature-
22 dependent spectral and/or temporal characteristics (such as a resonant wavelength),
23 with specific temperature-dependent behavior depending on the geometries of the slab
24 waveguide, of the channel waveguides, and of the diffractive elements, as well as the
25 thermo-optical and thermo-mechanical properties of the materials comprising the
26 apparatus. A spectral/temporal transfer function of the device may be obtained by
27 coherently summing the electric fields diffracted from the diffractive elements in the
28 channel waveguides. For a given vacuum wavelength λ , the resulting interference
29 depends on relative phase $\Delta\phi$ of portions of the optical signal back-diffracted from
30 different diffractive elements. This is illustrated schematically in Figure 16 (similar to
31 Figure 2). A portion of an incident optical signal is routed between optical ports 201 and

202 (points A and D, respectively) by back-diffraction from diffractive element subsets 205 in channel waveguides 204. Points of back-diffraction from two diffractive elements are represented by points C and C₁. Points B and B₁ designate the points where light is coupled into the channel waveguides 204 from the slab waveguide region 203 and then back into the slab waveguide region 203 after back-diffraction from the diffractive elements at points C and C₁ in the channel waveguides 204. The relative phase between light beams diffracted from points C and C₁ is calculated as:

$$\Delta\varphi = \frac{2\pi}{\lambda} ((n_{slab} \overline{AB} + 2n_{channel} \overline{BC} + n_{slab} \overline{BD}) - (n_{slab} \overline{AB_1} + 2n_{channel} \overline{B_1C_1} + n_{slab} \overline{B_1D})) \quad (1)$$

or equivalently

$$\Delta\varphi = \frac{2\pi}{\lambda} (n_{slab} \Delta L_{slab} + n_{channel} \Delta L_{channel}) \quad (2)$$

where ΔL_{slab} is difference in length between paths ABD and AB₁D, $\Delta L_{channel}$ is twice the difference in length between paths BC and B₁C₁, and n_{slab} and $n_{channel}$ are the effective refractive indexes of the specific waveguide mode in, respectively, the slab waveguide region 203 and the channel waveguides 204. In some instances ΔL_{slab} is sufficiently small so as to be negligible, but will be retained in this general treatment. The effective modal indexes are a function of the detailed waveguide geometry as well as the bulk indices, n_i , of the materials comprising the waveguides.

[0067] The condition for constructive interference for a resonance wavelength, λ_{res} , between two light rays reflected from points C and C₁ within the channel waveguides is then given by $\Delta\varphi = 2\pi m$, where $m = 1, 2, 3, \dots$ is an integer, yielding

$$\lambda_{res} = \frac{1}{m} (n_{slab} \Delta L_{slab} + n_{channel} \Delta L_{channel}) \quad (3)$$

Dependence of λ_{res} on temperature T is obtained by differentiating the above equation:

$$\begin{aligned} \frac{\partial \lambda_{res}}{\partial T} &= \frac{1}{m} \left(\Delta L_{slab} \frac{\partial n_{slab}}{\partial T} + n_{slab} \frac{\partial \Delta L_{slab}}{\partial T} + \Delta L_{channel} \frac{\partial n_{channel}}{\partial T} + n_{channel} \frac{\partial \Delta L_{channel}}{\partial T} \right) \\ &= \frac{\Delta L_{slab}}{m} \left(\frac{\partial n_{slab}}{\partial T} + n_{slab} \alpha_{slab} \right) + \frac{\Delta L_{channel}}{m} \left(\frac{\partial n_{channel}}{\partial T} + n_{channel} \alpha_{channel} \right), \quad (4) \end{aligned}$$

where α_{slab} ($\alpha_{channel}$) is an effective thermal expansion coefficient of the slab (channel) waveguide, $\alpha = \frac{1}{\Delta L} \frac{\partial \Delta L}{\partial T}$. The Eq. 4 provides a rule for designing devices with a pre-programmed temperature dependence of $\partial \mathcal{N} / \partial T$ (or other spectral or temporal characteristic). Substantially athermal operation is achieved when $\partial \mathcal{N} / \partial T$ is zero.

[0068] For further analysis it may be assumed for simplicity that the path length difference ΔL_{slab} is zero, which is achieved, for example, when the slab waveguide region 203 has an axis of symmetry and the input and output ports are located at equal distances from the axis of symmetry. The more general case of a non-zero ΔL_{slab} may be treated in a manner analogous to what follows. In the $\Delta L_{slab} = 0$ case, to achieve substantial independence of a resonance wavelength of the device from the temperature (the condition for substantially athermal operation), the following equation should be satisfied:

$$\left(\frac{\partial n_{channel}}{\partial T} + n_{channel} \alpha_{channel} \right) = 0. \quad (5)$$

If the channel waveguide is formed of k layers with uniform refractive index in each layer, then $n_{channel}$ is a function of the refractive indexes of all layers, i. e.

$$n_{channel} = n_{channel}(n_1, n_2, \dots, n_k). \quad (6)$$

The derivative of $n_{channel}$ with temperature can then be written generally as

$$\frac{\partial n_{channel}(n_1, n_2, \dots, n_k)}{\partial T} = \sum_{i=1}^k \varepsilon_i \frac{\partial n_i}{\partial T}, \quad (7)$$

where

$$\varepsilon_i = \frac{\partial n_{channel}}{\partial n_i}. \quad (8)$$

The values of the ε_i depend on all the material indices and the detailed channel waveguide geometry. The values of the ε_i parameters can be determined by standard calculational algorithms known in the art. The values of $\partial n_i / \partial T$ are characteristic of the materials utilized in the construction of the channel waveguide structure. The condition for substantially athermal operation may be re-written as:

$$\sum_{i=1}^k \varepsilon_i \frac{\partial n_i}{\partial T} + n_{channel} \alpha_{channel} = 0 \quad (9)$$

It is seen that by choosing materials with appropriate values of n_i and opposite signs of $\partial n_i / \partial T$ and adjusting the design parameters ε_i by varying the thickness of the layers forming the channel waveguide, one can achieve substantial independence of the from the temperature of device spectral and/or temporal characteristics. Alternatively, it is possible to vary the depth, width (in the propagation direction), and spacing (i.e., diffractive order) of the diffractive elements (collectively, the diffractive element geometry) to adjust the design parameters ε_i and achieve the desired temperature dependent characteristics of the device. For example, a first-order diffractive structure with diffractive-element width $\Lambda/2$ and period Λ may be changed to second order (i. e. with period approximately 2Λ), maintaining the same diffractive element width and operative device wavelength while altering the temperature dependence of the operative wavelength. It is also seen that these methods may be applied to set $\partial \lambda / \partial T$ to a designed value, thereby yielding an optical device with a programmed temperature dependence of its spectral and/or temporal characteristics.

[0069] Satisfying the athermal condition (Eq. 5 or Eq. 9) at some temperature within an operating temperature range does not necessarily ensure that the device will remain substantially athermal throughout that range. Both $\partial n_i / \partial T$ and ε_i may vary with temperature. Suitable choice of waveguide structure may be employed to balance the changes in $\partial n_i / \partial T$ against those in ε_i so as to reduce device temperature dependence over its operating range. The $\partial n_i / \partial T$ terms are set by material composition. The ε_i terms and their temperature dependences may be controlled by the geometry of the channel waveguide and/or the diffractive element geometry.

[0070] As seen from the condition for the athermal operation (Eq. 5 or 9), even if the materials comprising a planar waveguide optical device do not have opposite signs of the thermo-optical coefficient ($\partial n_i / \partial T$), it is still possible to design a substantially athermal device if terms involving ε_i and/or α have signs opposite the sign of the thermo-optical coefficient(s) of the material(s). Such an approach may be applicable in planar waveguides comprising various polymers and/or other materials where α and

1 $\partial n/\partial T$ have opposite signs and comparable magnitudes. In addition, the thermal
2 expansion term (α in Eqs. 5 and 9) may be adjusted using additional mechanical means
3 to compensate for changes in the refractive indices. For example, a bi-metallic plate
4 may be secured to the substrate of a planar waveguide device to create additional
5 temperature-dependent mechanical stress and/or strain. In the above examples, the
6 value of α - for substantially athermal operation is defined by

$$\alpha = -\left(\frac{1}{n_{channel}}\right) \sum_{i=1}^k \varepsilon_i \frac{\partial n_i}{\partial T}. \quad (10)$$

8 Further description of thermal compensation of the devices disclosed herein may be
9 found in the references cited herein.

10 **[0071]** It should be noted that many of the embodiments depicted in this disclosure are
11 only shown schematically, and that not all the features may be shown in full detail or in
12 proper proportion. Certain features or structures may be exaggerated relative to others
13 for clarity. In particular, it should be noted that the numbers of diffractive elements and
14 channel waveguides in an actual device may typically be larger than that shown in the
15 Figures. The numbers of diffractive elements and waveguides are reduced in the
16 Figures for clarity. It should be further noted that the embodiments shown in the Figures
17 are exemplary only, and should not be construed as specifically limiting the scope of the
18 written description or the claims set forth herein. It is intended that equivalents of the
19 disclosed exemplary embodiments and methods shall fall within the scope of the
20 present disclosure. It is intended that the disclosed exemplary embodiments and
21 methods, and equivalents thereof, may be modified while remaining within the scope of
22 the present disclosure.